

Windows 98 SE

Slot 1 Benchmarks	
Mainboard	ASUS P2B-F Rev. 1.00
RAM	256 MB SDRAM (PC100 CL2)
DirectX	9.0c

CPU		Grafikkarte		Treiber	3D Mark 99 Max		3D Mark 2000		PC Mark 2002		
Modell	Takt	Modell	RAM		3D Marks	CPU Marks	3D Marks	CPU Marks	CPU	RAM	HDD
Pentium III (SL35E)	500 MHz	ATi 3D Rage Pro	8 MB (64 Bit)		1881	7732					
Pentium III (SL35E)	500 MHz	ATi 3D Rage128 Pro (XPert 2000 Pro)	32 MB (64 Bit)		4551	7882					
Pentium III (SL35E)	500 MHz	ATi 3D Rage128 Pro (Rage Fury Pro)	32 MB (128 Bit)		4575	7838					
Pentium III (SL35E)	500 MHz	NVidia Riva TNT2 M64 (Ennyah Tech)	32 MB (64 Bit)	spez. Ennyah	4927	7880					
Pentium III (SL35E)	500 MHz	NVidia GeForce 4 MX 440	64 MB (128 Bit)	Forceware 81.98	3645	7771	3202	217			
Pentium III (SL35E)	500 MHz	NVidia GeForce 4 Ti 4200 (MSI MS-8894)	64 MB (128 Bit)	Forceware 81.98	3700	7833	3239	219			
Pentium III (SL37C)	450 MHz	NVidia GeForce 4 MX 440	64 MB (128 Bit)	Forceware 81.98	3299	7042	2918	197	1199	1070	712
Pentium II (SL2U7)	450 MHz	NVidia GeForce 4 MX 440	64 MB (128 Bit)	Forceware 81.98	2982	4338	2916	195	1175	1043	710

Windows 98 SE

SiSoft Sandra 2000 Standard			
CPU	Multi-Media	Memory	Drive Index
1205 MIPS 599 MFLOPS	MMX 1401 it/s SSE 1863 it/s	ALU 261 MB/s FPU 341 MB/s	20385
1197 MIPS 595 MFLOPS	MMX 1363 it/s FPU 635 it/s	ALU 254 MB/s FPU 319 MB/s	20277